



Technical Specifications

Technical Specifications

PT7135/37 詳細規格

型號	<ul style="list-style-type: none"> . PT7135 NTSC CCD . PT7137 PAL CCD 	尺寸	<ul style="list-style-type: none"> . 長:110mm . 寬: 110mm . 高: 130mm
系統	<ul style="list-style-type: none"> . CPU: VVTK-1000 SoC . RAM: 32MB SDRAM . ROM: 4MB FLASH ROM 	重量	<ul style="list-style-type: none"> . 淨重. 259g(pt7135)/271g(pt7137)
		聲音	<ul style="list-style-type: none"> . GSM-AMR/MPEG4 AAC . 支援靜音
網路	<ul style="list-style-type: none"> . 通訊協定 UPnP, TCP/IP, RTSP/RTP/RTCP,HTTP, SMTP, FTP, Telnet, NTP, DNS, DDNS, DHCP and PPPoE . 乙太網路 10 baseT or 100 baseT Fast Ethernet, auto negotiation . 無線乙太網路(PT7137) 802.11g 	電源	<ul style="list-style-type: none"> . 輸出: 12VDC
		操作環境	<ul style="list-style-type: none"> . 溫度: 0~40° C(32°~102° F) . 溼度: 85% RH
		垂直/水平	<ul style="list-style-type: none"> . 水平轉動+175°~ -175° . 垂直轉動+90°~ -35° , . 自動巡曳功能
		LED指示燈	<ul style="list-style-type: none"> . 電源及狀態指示 . 網路連接指示 . 麥克風狀態指示
攝影機規格	<ul style="list-style-type: none"> . 1/4 inch color CMOS sensor 640(H)x480(V) 1 Lux / F2.0 AGC, AWB, AES 電子快門:1/60~1/15,000sec. 	鏡頭	<ul style="list-style-type: none"> . 標準CS環型式4.0mm, F2.0
		麥克風	<ul style="list-style-type: none"> . 全方位接收 . 頻率 50 ~ 16000Hz . 噪訊比 More than 60dB
影像	<ul style="list-style-type: none"> . 解析度 Up to 30/25 frames at 160x120 Up to 30/25 frames at 176x144 Up to 30/25 frames at 320x240 Up to 30/25 frames at 640x480 . 演算法支援 MPEG4 simple profile/MJPEG selectable for streaming video JPEG for still image . 功能 Adjustable image size and quality and bit-rate Time stamp and text caption Three configurable motion detection windows Flip & mirror 	系統需求	<ul style="list-style-type: none"> . 作業系統: Microsfot Windows98 SE, ME, 2000, XP . 瀏覽器: Internet Explorer 5.0 or above . 手機:3GPP player . Real player 10.5 . Quick Time 6.5 . Packer Video Player 3.0
		防護措施	<ul style="list-style-type: none"> ID/Password 鑑定
		磁檢與安規	<ul style="list-style-type: none"> . CE, FCC